

## ECB01 OPTICAL FIBRE ENCLOSURE

This IP65 fibre enclosure offers the ability to terminate 8 fibres housed in a strong ABS enclosure, suitable for both indoor and outdoor applications and is lockable with a key. The enclosure has a detachable front door and hinged/detachable splice tray that allows for easy access during installation or re-work. There are 2 exit points and 1 incoming entry points, with integrated jubilee clip to ensure secure cable installation. Both the entry and exit points uphold the IP65 rating.

### FEATURES

- IP 65 rated
- Lockable front door
- Supports up to 8 fibres
- Detachable front door
- Hinged/detachable splice trays assists installation
- Accepts loose tube, distribution and pre-terminated cables
- Sealing glands for up to 8 cables
- Supplied with heat shrink splice protectors, wall fixings and cable ties.
- ROHS, REACH & SvHC materials compliant



### TECHNICAL SPECIFICATION

Height - Width - Depth	191mm x 120mm x 44mm
Net weight	0.404kg
Suitable for adaptor Type	SC simplex, LC duplex
Number of fibres	8
Number of ports	4
Cable Entry	1
Cable Exit	2
IP Rating	IP65
Designed in accordance with	TIA/EIA 568.C, ISO/IEC 11801, EN50173, IEC60304, IEC61754, EN297-1



Part Number: **ECB01**